



SWOOPER FLAG POLE ASSEMBLY / SAFETY INSTRUCTIONS

ASSEMBLY

Your flag pole & base should consist of three (3) metal poles (one curved and two straight), and either one Tire Base, one Trailer Hitch Adapter Base, one Fence Angle Base, one Fence Straight Base or one Ground Spike Base.

1. Connect the top of the bottom pole (straight pole with inserted metal pole smaller in diameter) to the middle pole (straight pole with same diameter throughout.)
2. Connect the bottom of the top pole (curved pole) into the other end of the middle pole.
3. Please check that the end of your curved top pole has a plastic cap to protect the pole from tearing the sleeve.
4. Starting with the end of the curved top pole, take the bottom of the flag sleeve (the bottom of the flag) and slip it over the curved top pole and then through the rest of the poles.

If you purchased the Tire Base: ***KICK*** the Tire Base stand under the tire. **Do not drive over the base.** Insert the poles and flag into Tire Base stand.

If you purchased the Ground Spike Base: hammer the Ground Spike into the ground. Next, insert the poles and flag into the ground spike.

SAFETY

Important safety tip: Remove the flag pole from the Tire Base stand ***FIRST***, ***then remove the base by hand before*** driving a vehicle (do not drive the vehicle before removing the base). Otherwise, the flag pole may tip over and cause damage or injury.

In high wind conditions, temporarily take your poles and flag down.